1. A device generating a random signal,

characterized in that

it includes a transient-state electronic circuit and furthermore means (112) to control the operation and/or the shutdown of said circuit in order to generate a random signal at said circuit's output.

- 2. Device as claimed in claim 1, characterized in that the circuit comprises semiconducting logic elements.
- Device as claimed in claim 2, characterized in that it comprises an
 oscillator circuit including semiconducting elements and means controlling operation and/or
 shutdown of said circuit.
- 4. Device as claimed in claim 3, characterized in that the output of the oscillator circuit (11) is looped (113) to its input.
- 5. Device as claimed in claim 4, characterized in that the oscillator circuit comprises means constituting the inverter (111) and inverting at its output (111a) the signal applied to its input (111b) and further includes a loop between its input and output.
- 6. Device as claimed in claim 5, characterized in that means controlling the operation or the shutdown of the oscillator circuit include means (112) acting as switches and situated in the loop between the output of the inverter-constituting means and the oscillator-circuit output.

20

20

8

8. A device comprising logic circuit(s) to generate a random signal, characterized in that

said device comprises several sub-assemblies (11a, 11b) claimed in one of the above claims for the purpose of continuously generating said random signal, furthermore elements (21, 22) to consecutive and alternatingly control the operation and the shutdown of the transient-state circuit of each of said elements, and also an element (20) to AND, OR or XOR the outputs from the different elements.

- 9. Device as claimed in claim 8, characterized in that the ANDing, ORing or XORing elements apply to the outputs of the different elements a gate of the EXCLU-SIVE OR type.
- Device as claimed in claim 9, characterized in that the control means include at least one counter (21) receiving at its input the output from the elements combining in turn ANDing, ORing or XORing the outputs of the different elements, further including means controlling the operation of the shutdown of the semiconducting elements of said devices as a function of the counter's countdown.
- Device as claimed in one of the above claims, characterized in that it is incorporated into a specific or into a programmable integrated circuit.